

PCT

WORLD INTELLECTUAL PROPERTY
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER 7


WO 9608799A1

(51) International Patent Classification ⁶ : G07F 17/34, A63F 5/04, 9/22		A1	(11) International Publication Number: WO 96/08799
			(43) International Publication Date: 21 March 1996 (21.03.96)
(21) International Application Number: PCT/AU95/00598		(81) Designated States: AU, CA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 12 September 1995 (12.09.95)			
(30) Priority Data: PM 8161 15 September 1994 (15.09.94) AU		Published With international search report.	
(71) Applicant (for all designated States except US): ARISTOCRAT LEISURE INDUSTRIES PTY. LTD. [AU/AU]; 85-113 Dunning Avenue, Rosebery, NSW 2018 (AU).			
(72) Inventor; and (75) Inventor/Applicant (for US only): BENNETT, Nicholas, Luke [AU/AU]; 18/22 Mosman Street, Mosman, NSW 2088 (AU).			
(74) Agent: F.B. RICE & CO.; P.O. Box 117, 28A Montague Street, Balmain, NSW 2041 (AU).			

(54) Title: MULTILINE GAMING MACHINE

(57) Abstract

A slot machine (50) is disclosed having a display matrix (51) of the type housing spinning reels or pseudo reels, and having a possible winning pay line all possible combinations of symbol positions which include one position in each column of the display. For an n row x m column display matrix the number of possible lines becomes n^m , each of which may be selected individually or in groups (54).



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

MULTILINE GAMING MACHINE

The present invention relates to gaming machines of the type generally referred to as slot machines, fruit machines or poker machines, and in particular the invention provides an improvement to a game played on such a machine.

Players who regularly play gaming machines quickly tire of particular games and therefore it is necessary for manufacturers of these machines to come up with innovative game features that add interest to the games provided on such machines in order to keep the players amused and therefore willing to continue playing the game.

Description of the Prior Art

Gaming or poker machines have been well known in the state of New South Wales for many years and have more recently gained considerable popularity throughout Australia, with quite substantial amounts of money wagered on these machines. There is a growing tendency for State governments to legalise the use of gaming machines by licensing operators, with resulting revenue gains through licence fees and taxation of monies invested. The licensed operation of gaming machines is the subject of State legislation and regulation. This regulation most always dictates a minimum percentage payout for a gaming machine. For example, a minimum of 85% of monies invested must be returned as winnings, and manufacturers of gaming machines therefore must design their machines around these regulatory controls.

With the growth that has occurred in the gaming machine market there is intense competition between manufacturers to supply the various existing and new venues. When selecting a supplier of gaming machines, the operator of a venue will often pay close attention to the popularity of various games with their patrons.

Therefore, gaming machine manufacturers are keen to devise games which are popular with players, as a mechanism for improving sales.

Many various strategies have been tried in the past
5 to make games more enticing to players, and these strategies are often aimed at either increasing the maximum prize payable on a machine or creating at least the perception of more winning opportunities. The present invention falls into the latter category. For quite a few
10 years, it has been possible to bet on more than one pay line of a slot machine simultaneously. However this feature has been restricted by the number of pay lines that could be achieved on the display format commonly used in slot machines.

15 The present invention provides an arrangement whereby

the number of pay lines provided on a slot machine, particularly a machine with 3x5 display, can be increased without changing the display format.

20 Summary of the Invention

The present invention consists in a gaming machine having display means arranged to display a plurality of symbols in an array of n rows and m columns, game control means arranged to control images displayed on the display
25 means the game control means being arranged to pay a prize when a predetermined combination of symbols is displayed on a line of symbols displayed on the display means, the gaming machine being characterised in that the number of lines for any one game is a value which is the product
30 $k_1 \dots k_i \dots k_m$ where k_i represents a number of symbol positions which has been selected by the player in an i th column of the display ($0 < j \leq n$), at least one symbol position being selected from each column, and the number of lines being the number of possible combinations of the
35 selected symbol positions which have one symbol position in each column of the display means.

The preferred embodiments of the invention use a display means which displays symbols in 3 rows and 3, 4 or 5 columns.

In a particular embodiment the number of lines for any one game is a value n^j where j is less than or equal to m , is directly or indirectly player selectable and represents a selected number of columns of the display means whereby each line is made up of m symbol positions one selected from each of the m columns, the lines used for a given value of j being all possible combinations using one symbol from each of j selected columns of the display means combined with the symbols in a predetermined row from the remaining $m-j$ columns.

In this embodiment, rather than individually selecting symbol positions, a player will select columns of symbol positions as a group. This arrangement has the advantage that the selection mechanism is simplified.

Preferably the display format will have three rows and the predetermined row from which the remaining $m-j$ symbol positions are selected is a centre row.

Preferably also the j columns will be a left most j columns of the display means.

The invention is equally applicable to video machines and machines employing spinning reels.

25 Brief Description of the Drawings

Embodiments of the present invention will now be described by way of example with reference to the accompanying drawings in which:

Figure 1, 2, 3 and 4 diagrammatically illustrates four possible embodiments of a 243 line multi-line pay arrangement for a machine with a 3x5 display format; and

Figures 5 and 6 illustrate two possible machine configurations in which the games described with reference to Figures 1 to 4 may be employed.

Detailed Description of the Preferred Embodiments

In the following detailed description, the methodology of the embodiments will be described and it is to be understood that it is within the capabilities of the non-inventive worker in the art to introduce the methodology on any standard microprocessor base gaming machine by means of appropriate programming.

Traditional slot machines have made use of spinning reels to provide a display function with symbols carried on the reels being aligned to produce a game result which may or may not be a winning combination. Traditionally such machines paid a prize only on a centre row combination, however over the years more complex pay arrangements have been developed in which winning combinations could appear on horizontal lines above and follow the centre row line, and later on diagonal lines (typically on 3 reel machines).

In more recent times video displays have been used to simulate spinning reels on these types of machines and in some instances machines have been provided with matrices of pseudo spinning wheels such as a 3x3 matrix of reels, whereby every single position on the display screen is essentially independently randomly achieved and therefore it was valid to pay on vertical combinations as well as horizontal combinations. In such a machine with a 3x3 symbol matrix display, winning combinations could be achieved on any one of three horizontal pay lines, three vertical paylines and two diagonals, making 8 possible lines on which a result could be assessed.

It is normal for machines of the type having multiple pay lines available, that the player would purchase the option of playing for a win on lines other than the centre line. That is to say, if the player wagered only one token he played only for a winning combination on one line, whereas if he wagered a number of

tokens he may well select to wager some of those tokens on lines other than the centre line of the display.

This mechanism adds interest to the game being played by the player as essentially it enables him to make multiple bets simultaneously.

Referring to Figure 1, a matrix symbolic of a typical three line by five column display matrix is illustrated, and it will be immediately apparent that in such an arrangement diagonal pay lines as conventionally used in 3x3 symbol matrix machines are not appropriate to the 3x5 format. Similarly, in slot machines which play games which follow the traditional format of a plurality of vertical spinning reels, vertical pay lines are not appropriate as there is no significant degree of randomness in the combinations provided on the vertical line.

Therefore, with this in mind the first embodiment of the present invention provides an arrangement for a slot machine having a 3x5 symbol matrix display with 243 possible pay lines being all possible combinations of symbol positions which include one position in each column of the display.

Referring to Figure 1 a 3x5 display matrix is illustrated and in this embodiment a player may select the symbol positions to be included in their pay line combinations. If the symbol positions marked with an 'x' in Figure 1 are selected by the player (ie AX, AY, AZ, BY, CX, CY, DY, DZ, EY) then the corresponding pay lines will be as shown in Table 1.

TABLE 1

<u>LINE NO</u>	<u>DISPLAY POSITIONS USED</u>
1	AX BY CX DY EY
2	AX BY CX DZ EY
3	AX BY CY DY EY

	4	AX	BY	CY	DZ	EY
	5	AY	BY	CX	DY	EY
	6	AY	BY	CX	DZ	EY
	7	AY	BY	CY	DY	EY
15	8	AY	BY	CY	DZ	EY
	9	AZ	BY	CX	DY	EY
	10	AZ	BY	CX	DZ	EY
	11	AZ	BY	CY	DY	EY
	12	AZ	BY	CY	DZ	EY

10 It will be seen that the number of lines produced is given by the product

$$k_1 \times k_2 \times k_3 \times k_4 \times k_5$$

where k_i is the number of symbol positions selected in the i^{th} column of the machine. For an m column display
15 the number of lines would be represented by the product

$$k_1 \times k_2 \times \dots \times k_i \times \dots \times k_m.$$

In the embodiment of Figure 1 the centre line symbol positions are always selected, however it is also possible to produce embodiments in which any single symbol position
20 might be selected in each column and such an embodiment is illustrated in figure 2. In this embodiment lines 1,2,5,6,9 and 10 defined in Table 1 will be effective for the symbol positions selected (as marked with a 'x'). In the embodiment of Figure 2 the selection would default to
25 the centre line position in the event that no symbol was selected in a particular column.

Selection of symbol positions for inclusion on pay lines may be achieved using a number of methods such as placing a touch sensitive layer over each symbol position
30 in the display, or providing a matrix of buttons corresponding to the display matrix format.

Figures 3 and 4 illustrate a simplified version of the invention in which players may select columns of symbol positions to be included in their pay line
35 combinations. These embodiments are simpler than those previously described because only one selection mechanism

is required per display column. Selection might be by way of touch sensitive membrane over the display or by way of a switch under each column.

In the embodiment of Figure 3 columns must be selected from the left such that if 3 lines are required column A is selected, if 9 lines are required column B is selected (and column A will be automatically selected), and similarly for 27 lines (column C), 81 lines (column D) and 243 lines (column E). The lines provided when 9 lines are selected are defined in Table 2.

TABLE 2

	<u>LINE NO</u>	<u>DISPLAY POSITIONS USED</u>
15	1	AX BX CY DY EY
	2	AX BY CY DY EY
	3	AX BZ CY DY EY
	4	AY BX CY DY EY
	5	AY BY CY DY EY
20	6	AY BZ CY DY EY
	7	AZ BX CY DY EY
	8	AZ BY CY DY EY
	9	AZ BZ CY DY EY

In the embodiment of Figure 4 there is no restriction on which columns are selected and therefore the player must indicate each column to be included. The lines selected in Figure 4 are defined in Table 3.

TABLE 3

	<u>LINE NO</u>	<u>DISPLAY POSITIONS USED</u>
30	1	AY BX CY DY EX
	2	AY BX CY DY EY
	3	AY BX CY DY EZ
35	4	AY BY CY DY EX
	5	AY BY CY DY EY

6	AY	BY	CY	DY	EZ
7	AY	BZ	CY	DY	EX
8	AY	BZ	CY	DY	EY
9	AY	BZ	CY	DY	EZ

5 It will be seen that the number of lines produced in the embodiments of Figures 3 and 4 is given by nj

where n is the number of display rows and j is the number of columns selected ($0 \leq j \leq m$)

10 Referring to Figure 5, a slot machine 50 is illustrated in which symbol positions are selected for inclusion in pay lines by way of a touch sensitive membrane applied over the display screen 51, the membrane being divided into a number of switch panels 52 each of
15 which corresponds with one display position of the display 51. This arrangement can be used to implement the embodiments described with reference to Figures 1 and 2.

Each vertical set of touch sensitive panels 52 can be operated in parallel in the embodiments of Figures 3
20 and 4, such that columns of display positions can be selected by touching any switch over the respective column. Alternatively, each set of three vertically aligned switches may be implemented as a single touch panel running over the entire column of display positions.

25 When implementing the embodiments described with reference to Figures 3 and 4, it is also possible to dispense with the touch switches and use the switches 53 located below the display area.

The machine of Figure 5 is illustrated with a video
30 display but may also make use of a display comprising a plurality of stepping motor driven reels carrying a plurality of symbols.

Turning now to Figure 6, a further slot machine configuration is shown in which the slot machine 50 is
35 provided with a display 51, which may be either a video display or a stepper motor driven reel display and a

matrix of switches 54 corresponding to the format of the display matrix, such that symbol positions can be selected by use of the matrix 54 to define the pay lines applicable for a game played on the machine. This arrangement can be
5 used for the embodiments described with reference to Figures 1 and 2.

It will be recognised that other switch configurations may also be employed which multiplex switch functions to reduce the number of switches required.

10 It will also be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present
15 embodiments are, therefore, to be considered in all respects as illustrative and not restrictive.

CLAIMS:-

1. A gaming machine having display means arranged to display a plurality of symbols in an array of n rows and m columns, game control means arranged to control images
5 displayed on the display means the game control means being arranged to pay a prize when a predetermined combination of symbols is displayed on a line of symbols displayed on the display means, the gaming machine being characterised in that the number of lines for any one game
10 is a value which is the product $k_1 \dots k_2 \dots k_m$ where k_1 represents a number of symbol positions which has been selected by the player in an i^{th} column of the display ($0 < j \leq n$), at least one symbol position being selected from each column, and the number of lines being the number of
15 possible combinations of the selected symbol positions which have one symbol position in each column of the display means.
2. The gaming machine as claimed in claim 1 wherein the number of lines for any one game is a value n^j where j is
20 less than or equal to m , is directly or indirectly player selectable and represents a selected number of columns of the display means whereby each line is made up of m symbol positions one selected from each of the m columns, the lines used for a given value of j being all possible
25 combinations using one symbol from each of j selected columns of the display means combined with the symbols in a predetermined row from the remaining $m-j$ columns.
3. The gaming machine of claim 2 wherein the display format has three rows and the predetermined row from which
30 the remaining $m-j$ symbol positions are selected is a centre row.
4. The gaming machine of claim 2 wherein the j columns are the left most j columns of the display means.
5. The gaming machine of claim 3 wherein the display
35 means is arranged to display symbols in 3 rows and 3 columns.

6. The gaming machine of claim 3 wherein the display means is arranged to display symbols in 3 rows and 4 columns.
7. The gaming machine of claim 3 wherein the display means is arranged to display symbols in 3 rows and 5 columns.
8. The gaming machine as claimed in claim 1 wherein the player is able to select any number of symbol positions in any column of the display with a predetermined position being selected by the machine in any column in which the player does not make a selection, and where the lines used in a given game are all possible symbol position combinations having one position selected from each column of the display.
9. The gaming machine of claim 8 wherein the predetermined position selected by the machine is in the centre row of the display.
10. The gaming machine of claim 9 wherein the display means is arranged to display symbols in 3 rows and 3 columns.
11. The gaming machine of claim 9 wherein the display means is arranged to display symbols in 3 rows and 4 columns.
12. The gaming machine of claim 9 wherein the display means is arranged to display symbols in 3 rows and 5 columns.




FIG. 1




FIG. 2




FIG. 3





FIG. 4

**FIG. 5**




FIG. 6

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/AU 95/00598

A. CLASSIFICATION OF SUBJECT MATTER

Int Cl⁶: G07F 17/34, A63F 5/04, 9/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC : G07F 17/34, A63F 5/04, 9/00, 9/22

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
AU : IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	AU 82126/75 (500709) B (BALLY MANUFACTURING CORP) 16 December 1976 See page 5 line 20 to page 8 line 14	1-7
A	GB 2258334 A (KEANE) 3 February 1993 See page 6 line 24 to page 7 line 29	1-7
A	GB 2137392 A (JPM LTD) 3 October 1984 See page 2 lines 30-83	1-7

☒ Further documents are listed in the continuation of Box C

☒ See patent family annex

<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>		<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>
--	--	---

Date of the actual completion of the international search
27 November 1995

Date of mailing of the international search report

8 DECEMBER 1995

Name and mailing address of the ISA/AU
AUSTRALIAN INDUSTRIAL PROPERTY ORGANISATION
PO BOX 200
WODEN ACT 2606
AUSTRALIA Facsimile No.: (06) 285 3929

Authorized officer

S. CLARK

Telephone No.: (06) 283 2164

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/AU 95/00598

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2119989 A (NOBLE) 23 November 1983 See whole document	1,2
A	GB 2187320 A (DIRE et al) 3 September 1987 See page 1 line 37 to page 2 line 65	1,2
A	GB 2150844 A (ELLIS) 10 July 1985 See whole document	1-7

INTERNATIONAL SEARCH REPORT
Information on patent family members

International Application No.
PCT/AU 95/00598

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
AU	82126/75	AT	4805/75	DE	2527724	DK	2833/75
		JP	51017834	LU	72796	NL	7507521
		NO	752231	SE	7507168	US	4648600
GB	2187320	AU	68550/87	CA	1265870	JP	62275482
		US	4756531				
END OF ANNEX							

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)